RISEN

RISEN MACHINE

Brass valves&fittings,Fluid control system

中国·浙江
Zhejiang·China

About Risen

COMPANY INTRODUCE

Main product: Ball valves, Heating accessories and valves, Bibcocks, Fittings and spare parts

Establishment: in 2005, $28,000,000 annual export

Certifications: CQC,SGS,CE

Factory: 200 employees, 16,000m² workshop

Facility: 20 sets forging machine, 200 sets CNC machine, 5 automatic assembling lines

Capacity: 3,600 tons/year

Professional team: Research&Development, Produce process, Quality Control, Pre-after sale service

Brand:OBM, ODM, OEM

RISEN VALVE

Time Tells Honesty, Honesty Makes Top Quality

ISO9001 TUV SGS CE ACS WRAS

RS-5001





DN	SIZE	A	B	C	D
15	1/2"	47	45	85	14
20	3/4"	55	48	85	19
25	1"	64	56	103	23
32	1 1/4"	75	70	120	30
40	1 1/2"	88	75	120	38
50	2"	100	87	150	47
65	2 1/2"	120	113	215	57
80	3"	148	130	215	69
100	4"	171	145	295	85
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5002





DN	SIZE	A	B	C	D
15	1/2"	54	45	85	14
20	3/4"	59	48	85	19
25	1"	74	56	103	23
32	1 1/4"	82	70	120	30
40	1 1/2"	97	75	120	38
50	2"	111	87	150	47
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5003





DN	SIZE	A	B	C	D
15	1/2"	58	45	85	14
20	3/4"	64	48	85	19
25	1"	78	56	103	23
32	1 1/4"	86	70	120	30
40	1 1/2"	101	75	120	38
50	2"	115	87	150	47
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5004





DN	SIZE	A	B	C	D
15	1/2"	78	45	85	14
20	3/4"	85	48	85	19
25	1"	96	56	103	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5005





DN	SIZE	A	B	C	D
15	1/2"	47	38	52	14
20	3/4"	55	42	52	19
25	1"	64	52	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5006





DN	SIZE	A	B	C	D
15	1/2"	54	38	52	14
20	3/4"	59	42	52	19
25	1"	74	52	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5007





DN	SIZE	A	B	C	D
15	1/2"	58	38	52	14
20	3/4"	64	42	52	19
25	1"	78	52	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5008





DN	SIZE	A	B	C	D
15	1/2"	78	38	52	14
20	3/4"	85	42	52	19
25	1"	96	52	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5009





DN	SIZE	A	B	C	D
15	1/2"	48	50	90	13.5
20	3/4"	57	53	90	18
25	1"	68	62	105	23
32	1 1/4"	75	72	135	30
40	1 1/2"	89	78	135	37
50	2"	106	86	150	46
65	2 1/2"	122	113	217	58
80	3"	150	131	217	69
100	4"	173	147	298	84
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5010





DN	SIZE	A	B	C	D
15	1/2"	54	50	90	13.5
20	3/4"	63	53	90	18
25	1"	72	62	105	23
32	1 1/4"	83	72	135	30
40	1 1/2"	95	78	135	37
50	2"	113	86	150	46
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5011





DN	SIZE	A	B	C	D
15	1/2"	53	50	90	13.5
20	3/4"	61	53	90	18
25	1"	70	62	105	23
32	1 1/4"	82	72	135	30
40	1 1/2"	93	78	135	37
50	2"	109	86	150	46
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5012





DN	SIZE	A	B	C	D
15	1/2"	73	45	85	13.5
20	3/4"	82	48	85	18
25	1"	90	56	103	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5013





DN	SIZE	A	B	C	D
15	1/2"	48	37	52	13.5
20	3/4"	57	41	52	18
25	1"	68	50	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5014





DN	SIZE	A	B	C	D
15	1/2"	56	37	52	13.5
20	3/4"	65	41	52	18
25	1"	77	50	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5015





DN	SIZE	A	B	C	D
15	1/2"	53	37	52	13.5
20	3/4"	61	41	52	18
25	1"	70	50	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5016

RS-5017





DN	SIZE	A	B	C	D
15	1/2"	47	50	93	14
20	3/4"	54	60	93	17
25	1"	64	68	111.5	22
32	1 1/4"	72	78	137	29
40	1 1/2"	88.5	83	137	37
50	2"	101	97	165	44
65	2 1/2"	112	110	210	55
80	3"	135	127	210	67
100	4"	152	138	288	82
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5018





DN	SIZE	A	B	C	D
15	1/2"	55	50	93	14
20	3/4"	65.5	60	93	17
25	1"	70	68	111.5	22
32	1 1/4"	78.5	78	130	29
40	1 1/2"				
50	2"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5019





DN	SIZE	A	B	C	D
15	1/2"	55	50	93	14
20	3/4"	60.5	60	93	17
25	1"	70	68	111.5	22
32	1 1/4"				
40	1 1/2"				
50	2"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5020





DN	SIZE	A	B	C	D
15	1/2"	73	37	52	13.5
20	3/4"	82	41	52	18
25	1"	90	50	68	23
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	





DN	SIZE	A	B	C	D
15	1/2"	72	50	90	14
20	3/4"	85	60	93	17
25	1"	101	68	111.5	22
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5021





DN	SIZE	A	B	C	D
15	1/2"	47	42	51	14
20	3/4"				
25	1"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(110℃)	

RS-5022





DN	SIZE	A	B	C	D
15	1/2"	55	39	51	14
20	3/4"	65.5	42	51	17
25	1"	70	54.5	62	22
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5023





DN	SIZE	A	B	C	D
15	1/2"	55	42	58	14
20	3/4"	65.5	44.5	58	17
25	1"	70	53	68	22
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5024





DN	SIZE	A	B	C	D
15	1/2"	72	39	51	14
20	3/4"	85	42	51	17
25	1"	101	54.5	62	22
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5025





DN	SIZE	A	B	C	D
8	1/4"	40	33	60	8
10	3/8"	45	33	60	10
15	1/2"	50.5	42	84.5	13.5
20	3/4"	56	45.5	92	17
25	1"	68	56.5	104.5	22.5
32	1 1/4"	75	72	112	30
40	1 1/2"	94.5	79	120	37
50	2"	93.5	87	130	42
65	2 1/2"	128	116	207	53
80	3"	162	133	207	64
100	4"	179	149	281	82
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5026





DN	SIZE	A	B	C	D
8	1/4"	43.5	41.5	78.5	8
10	3/8"	52	41.5	78.5	10
15	1/2"	57	42	84.5	13.5
20	3/4"	62	45.5	92	17
25	1"	73	57	104.5	22.5
32	1 1/4"	80	75	112	30
40	1 1/2"	98	82	120	37
50	2"	104	91	130	42
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5027





DN	SIZE	A	B	C	D
15	1/2"	60	42	84.5	13.5
20	3/4"				
25	1"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5028





DN	SIZE	A	B	C	D
15	1/2"	49.5	47	97	14
20	3/4"	60.5	52	97	19
25	1"	66	58	112	24
32	1 1/4"	74	70	137	30
40	1 1/2"	86	79	137	37
50	2"	96.5	90	165	47
65	2 1/2"	122	115	210	57
80	3"	146	128	210	69
100	4"	169	140	292	85
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5029





DN	SIZE	A	B	C	D
8	1/4"	40	41	40	8
10	3/8"	45	41	40	10
15	1/2"	50.5	43	45	13.5
20	3/4"	56	47	45	17
25	1"	68	51	51.5	22.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5030





DN	SIZE	A	B	C	D
8	1/4"	43.5	41	40	8
10	3/8"	52	41	40	10
15	1/2"	57	43	45	13.5
20	3/4"	62	47	45	17
25	1"	73	51	51.5	22.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5031

RS-5033





DN	SIZE	A	B	C	D
15	1/2"	52	35	52	15
20	3/4"	59.5	42.5	65.5	20
25	1"	72	47	65.5	24.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5034





DN	SIZE	A	B	C	D
15	1/2"	59.5	44.5	90	14
20	3/4"	67.5	44.5	90	17
25	1"	79.5	58.5	101	22.5
32	1 1/4"				
40	1 1/2"				
50	2"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5035



DN	SIZE	A	B	C	D
15	1/2"	60	43	45	13.5
20	3/4"				
25	1"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5032



DN	SIZE	A	B	C	D
15	1/2"	53	46	87	14
20	3/4"	61	49	87	19
25	1"	69	58.5	105	23
32	1 1/4"				
40	1 1/2"				
50	2"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	



DN	SIZE	A	B	C	D
15	1/2"	69.3	40	67.6	14
20	3/4"				
25	1"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5036



DN	SIZE	A	B	C	D
15	1/2"	130	14	32	55.5
20	3/4"				
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5037



DN	SIZE	A	B	C	D
15	1/2"	80	43	87	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5038



DN	SIZE	A	B	C	D
15	1/2"	80	40	50	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5039



DN	SIZE	A	B	C	D
15	1/2"x1/2"	55	69	52.5	15
20	3/4"x3/4"	69	82	52.5	20
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5040



DN	SIZE	A	B	C	D
15	1/2"	85	50	78	10
20	3/4"	91	62.5	78	12
25	1"	108	77	86	19
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5041



DN	SIZE	A	B	C	D
15	1/2"	53	41	80	15
20	3/4"	60.5	46	102	20
25	1"	73	50	112	24.5
32	1 1/4"	78	61.5	116	30
40	1 1/2"	92.5	65	150	40
50	2"	110.5	72	150	50
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5042



DN	SIZE	A	B	C	D
15	1/2"x10mm	54	31.5	41	8
15	1/2"x12mm	54	31.5	41	8
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5043



DN	SIZE	A	B	C	D
10	3/8"	70	33.5	63	6.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5044



DN	SIZE	A	B	C	D
10	3/8"	84.5	38.5	12	7.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

GAS BALL VALVE

RS-5045



DN	SIZE	A	B	C	D
15	1/2"	58.5	47	98.5	15
20	3/4"	57	51	86	19
25	1"	68	60	105	24
32	1 1/4"	79	74	127	31
40	1 1/2"	92	80	127	38.5
50	2"	105	93	159	48
65	2 1/2"	128	119	217	58
80	3"	153	140	217	69
100	4"	177	153	296	87
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5046

RS-5049



DN	SIZE	A	B	C	D
15	1/2"	44.5	42	95	14
20	3/4"	51.5	48	95	17
25	1"	54	53	105	20
32	1 1/4"	66	66.5	132	25
40	1 1/2"	75.5	73.5	142	30
50	2"	98	81.5	152	44
80	3"				
100	4"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5050





DN	SIZE	A	B	C	D
15	1/2"	68	36.5	33	5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5047





DN	SIZE	A	B	C	D
20	3/4"	65	33.5	63	6.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5048





DN	SIZE	A	B	C	D
10	3/8"	84.5	38.5	12	7.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	





DN	SIZE	A	B	C	D
15	1/2"	49.5	48	102	14
20	3/4"	56.5	53	102	19
25	1"	68	56.5	102	24
40	1 1/2"	89	76	115	37
50	2"	105	86	125	47
80	3"	149	137.5	230	75
100	4"	173	150	230	93
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5051





DN	SIZE	A	B	C	D
15	1/2"	55	48	95	15
20	3/4"	66	53	95	20
25	1"	71.5	68	115	25
32	1 1/4"	82.5	75	135	29
40	1 1/2"	89	82	135	37
50	2"	100	86	165	40
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5052





DN	SIZE	A	B	C	D
15	1/2"	59.5	44.5	90	14
20	3/4"	65	47	94.5	18
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5053





DN	SIZE	A	B	C	D
15	1/2"	52	35	52	15
20	3/4"	59.5	42.5	65.5	20
25	1"	72	47	65.5	24.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5054





DN	SIZE	A	B	C	D
15	1/2"	67	37	53.5	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5055





DN	SIZE	A	B	C	D
15	1/2"	55	35	46.5	8.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5056





DN	SIZE	A	B	C	D
15	1/2"	57.5	35	46.5	8.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5057





DN	SIZE	A	B	C	D
8	1/4"				
10	3/8"				
15	1/2"	49	32	27	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5058





DN	SIZE	A	B	C	D
8	1/4"	41	32	26	6
10	3/8"	41	32	26	8
15	1/2"	43	32	26	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5059





DN	SIZE	A	B	C	D
8	1/4"	30.5	22.5	25.5	6
10	3/8"				
15	1/2"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5060





DN	SIZE	A	B	C	D
8	1/4"				
10	3/8"	66	31	23.5	9
15	1/2"	66	31	23.5	9
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

MINI BALL VALVE

RS-5061



DN	SIZE	A	B	C	D
8	1/4"	45	28	20	8
10	3/8"	45	28	20	8
15	1/2"	45	30	20	10
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5062



DN	SIZE	A	B	C	D
8	1/4"	40.5	25	26	10
10	3/8"	40.5	26	26	10
15	1/2"	44	28	26	10
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5063



DN	SIZE	A	B	C	D
8	1/4"	42	25.5	25.5	6
10	3/8"	46	26.5	25.5	8
15	1/2"	48	29	25.5	10
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5064



DN	SIZE	A	B	C	D
8	1/4"	36.5	24.5	25.5	6
10	3/8"				
15	1/2"				
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5065



DN	SIZE	A	B	C	D
20	3/4"	76	49	93	12
25	1"	82	52	104	15
32	1 1/4"	96	60	115	19
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5066



DN	SIZE	A	B	C	D
15	1/2"	70	42	84.5	13.5
20	3/4"	75.5	45.5	92	17
25	1"	91.5	56.5	104.5	22.5
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5067



DN	SIZE	A	B	C	D
15	1/2"	63	42	84.5	13.5
20	3/4"	70.5	45.5	92	17
25	1"	84	56.5	104.5	22.5
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5068



DN	SIZE	A	B	C	D
15	1/2"	55.5	47.5	92.5	15
20	3/4"	59.5	50.5	92.5	19
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

BALL VALVE

RS-5069



DN	SIZE	A	B	C	D
	15mm	64	40	87	12
	18mm	65	40	87	14
	22mm	73.5	45	105	19
	28mm	92	56	115	23
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
30		30bar(-10℃ to110℃)		5bar(150℃)	

RS-5070



DN	SIZE	A	B	C	D
	25mmx25mm	96	51	99.5	25.5
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5071



DN	SIZE	A	B	C	D
15	1/2"	69	41.5	84.5	8
20	3/4"	70.5	42.5	84.5	12
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5072

RS-5073



DN	SIZE	A	B	C	D
20	3/4"	88	45.5	55	14.5
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5074



DN	SIZE	A	B	C	D
15	1/2"	62	31	23.5	9
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5075



DN	SIZE	A	B	C	D
15	1/2"	62.5	40	51.5	15
20	3/4"	70	48	51.5	17.5
Pressure and temperature limitations for PN rated value					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to110℃)		800psi(150℃)	

RS-5076



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>20</td><td>3/4"</td><td>55.5</td><td>46.5</td><td>92.5</td><td>18</td></tr>
<tr><td>25</td><td>1"</td><td>68</td><td>56.5</td><td>102</td><td>22.5</td></tr>
<tr><td>32</td><td>1 1/4"</td><td>72.5</td><td>62.5</td><td>136</td><td>30</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"</td><td>50.5</td><td>43.5</td><td>45</td><td>13.5</td></tr>
<tr><td>20</td><td>3/4"</td><td>56</td><td>47</td><td>45</td><td>17</td></tr>
<tr><td>25</td><td>1"</td><td>68</td><td>51</td><td>51.5</td><td>22.5</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

BALL VALVE

RS-5077



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>32x20</td><td>32x3/4"</td><td>103</td><td>47</td><td>67</td><td>20</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">800psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5078



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"</td><td>74</td><td>44</td><td>67</td><td>15</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5079



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>20</td><td>3/4"</td><td>71.5</td><td>43.5</td><td>43.5</td><td>15</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5080



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"</td><td>98.5</td><td>55</td><td>54</td><td>15</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5081



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"</td><td>53</td><td>37.5</td><td>39</td><td>14.5</td></tr>
<tr><td>20</td><td>3/4"</td><td>63</td><td>39.5</td><td>39</td><td>19</td></tr>
<tr><td>25</td><td>1"</td><td></td><td></td><td></td><td></td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5082



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>8</td><td>1/4"</td><td>52</td><td>28</td><td>28</td><td>6</td></tr>
<tr><td>15</td><td>1/2"</td><td></td><td></td><td></td><td></td></tr>
<tr><td>20</td><td>3/4"</td><td></td><td></td><td></td><td></td></tr>
<tr><td>25</td><td>1"</td><td></td><td></td><td></td><td></td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5083



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"x3/4"</td><td>53</td><td>33</td><td>30.5</td><td>12</td></tr>
<tr><td>20</td><td>3/4"x1"</td><td></td><td></td><td></td><td></td></tr>
<tr><td>25</td><td>1"x1 1/4"</td><td></td><td></td><td></td><td></td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5084



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"x3/4"</td><td>52.5</td><td>42</td><td>30.5</td><td>16</td></tr>
<tr><td>20</td><td>3/4"x1"</td><td></td><td></td><td></td><td></td></tr>
<tr><td>25</td><td>1"x1 1/4"</td><td></td><td></td><td></td><td></td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">400psi(-10℃ to110℃)</td><td colspan="2">800psi(150℃)</td></tr>
</table>

RS-5085



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"x3/4"</td><td>88</td><td>80</td><td>87</td><td>10</td></tr>
<tr><td>20</td><td>3/4"x1"</td><td>98</td><td>86</td><td>87</td><td>12.5</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">12bar(-10℃ to 80℃)</td><td colspan="2">5bar(120℃)</td></tr>
</table>

RS-5086



<table>
<tr><th>DN</th><th>SIZE</th><th>A</th><th>B</th><th>C</th><th>D</th></tr>
<tr><td>15</td><td>1/2"x3/4"</td><td>88</td><td>75</td><td>50</td><td>10</td></tr>
<tr><td>20</td><td>3/4"x1"</td><td>98</td><td>86</td><td>50</td><td>12.5</td></tr>
<tr><td colspan="6">Pressure and temperature limitations for PN rated valve</td></tr>
<tr><td colspan="2">PN</td><td colspan="2">Pressure and temperature range</td><td colspan="2">Pressure and Max temperature</td></tr>
<tr><td colspan="2">≤ 1.6Mpa</td><td colspan="2">12bar(-10℃ to 80℃)</td><td colspan="2">5bar(120℃)</td></tr>
</table>

RS-5087





DN	SIZE	A	B	C	D
15	1/2"x3/4"	89	84	78	10
20	3/4"x1"	97	86	78	12
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5088





DN	SIZE	A	B	C	D
15	1/2"x3/4"	91	89	64.5	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

BIBCOCK

RS-8005





DN	SIZE	A	B	C	D
15	1/2"x3/4"	87	85	82	13
20	3/4"x1"	91	86	87	13
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-8006





DN	SIZE	A	B	C	D
15	1/2"x3/4"	73	82	86	10
20	3/4"x1"	101.5	94.5	86	12
25	1"x1 1/4"	116.5	104.5	86	14
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-8007





DN	SIZE	A	B	C	D
15	1/2"x3/4"	89	81.5	52	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-8008





DN	SIZE	A	B	C	D
15	1/2"x3/4"	85.5	82	92	10
20	3/4"x3/4"	85.5	82	92	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5089





DN	SIZE	A	B	C	D
15	1/2"	104.5	95.5	97	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5090





DN	SIZE	A	B	C	D
15	1/2"	104.5	95.5	97	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5091





DN	SIZE	A	B	C	D
15	1/2"x3/4"	95	86		13.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5092





DN	SIZE	A	B	C	D
15	1/2"	146	87.5		15.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

BIBCOCK

RS-5093





DN	SIZE	A	B	C	D
15	1/2"	57	42	51.5	8
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5094

RS-5097





DN	SIZE	A	B	C	D
15	1/2"x3/4"	91.5	76.5	60	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5098



DN	SIZE	A	B	C	D
15	1/2"x3/4"	93	99.5	64.5	10
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5095



DN	SIZE	A	B	C	D
15	1/2"	100	80	50	14.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to 110℃)		600psi(150℃)	

RS-5096



DN	SIZE	A	B	C	D
15	1/2"	75.5	71	77.5	
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	



DN	SIZE	A	B	C	D
15	1/2"x3/4"	91.5	76.5	60	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5099



DN	SIZE	A	B	C	D
15	1/2"	73.5	59	60	14.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5100



DN	SIZE	A	B	C	D
15	1/2"x3/4"		104	54.5	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

BIBCOCK

RS-5101



DN	SIZE	A	B	C	D
15	1/2"x3/4"	95	110	41	7
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5102



DN	SIZE	A	B	C	D
15	1/2"x3/4"	97	118	44	14.5
20	3/4"x3/4"	97	118	44	14.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5103



DN	SIZE	A	B	C	D
15	1/2"x3/4"	88.5	119	45	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5104



DN	SIZE	A	B	C	D
15	1/2"x3/4"	95	110	41	7
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		12bar(-10℃ to 80℃)		5bar(120℃)	

ISO9001 TUV SGS CE ACS WRAS

GATE VALVE

RS-5105



DN	SIZE	A	B	C	D
15	1/2"	44	71.5	47.5	15
20	3/4"	48	75.5	47.5	17
25	1"	62	102	69	24
32	1 1/4"	65	109	73	30
40	1 1/2"	71	123	87	37
50	2"	78	137	98	46
65	2 1/2"	80	168	98	59
80	3"	85	189	105	68
100	4"	102	236	122	84
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5106



DN	SIZE	A	B	C	D
15	1/2"	48	77	54	15
20	3/4"	52	85	60	20
25	1"	58	99.5	70	25
32	1 1/4"	61	106	75	30
40	1 1/2"	68	120.5	90	38
50	2"	73	132	100	48
65	2 1/2"	73	166	100	60
80	3"	81	183	110	70
100	4"	95	233	125	86
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5107



DN	SIZE	A	B	C	D
15	1/2"	48	76	54	15
20	3/4"	52	78	54	20
25	1"	58	90	57	25
32	1 1/4"	61	104	73	30
40	1 1/2"	68	118	73	38
50	2"	73	127	80	48
65	2 1/2"	73	161	90	60
80	3"	81	175	102	70
100	4"	95	224	113	86
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5108



DN	SIZE	A	B	C	D
15	1/2"	45	76.5	53.5	14.5
20	3/4"	48	88	59.2	20
25	1"	54	97	64.5	25
32	1 1/4"	60	112	74	32
40	1 1/2"	64	130	80	37
50	2"	72	150	89	47
65	2 1/2"	80	185	110.5	58
80	3"	84	210.5	120	65
100	4"	103	259.5	140.5	91
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5109



DN	SIZE	A	B	C	D
15	1/2"	40	72	55	14
20	3/4"	45	81	55	19
25	1"	48	90	60	24
32	1 1/4"	53	92	70	29
40	1 1/2"	60.5	95	70	33
50	2"	69	112	80	48
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5110



DN	SIZE	A	B	C	D
15	1/2"	42	74.5	55	13
20	3/4"	47.5	85	55	19.5
25	1"	50	97	60	25
32	1 1/4"	57	109	70	29.5
40	1 1/2"	63	120.5	70	37
50	2"	71.5	132	80	49
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5111



DN	SIZE	A	B	C	D
15	1/2"	43	73.5	47	13
20	3/4"	46	76	47	18
25	1"	58	85	53	24
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5112



DN	SIZE	A	B	C	D
20	3/4"	52	77	54	19
25	1"	58	85	60	25
32	1 1/4"	59	99.5	71	30.5
40	1 1/2"	57	106	75	36
50	2"	64.5	120.5	90	47
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

GATE VALVE

RS-5113



DN	SIZE	A	B	C	D
15	1/2"	45	75	47	13
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5114



DN	SIZE	A	B	C	D
15	1/2"				
20	3/4"	56	68	48	15
25	1"				
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5115



DN	SIZE	A	B	C	D
15	15MM	54	63.5	50	13.5
20	22MM	58.5	70.5	50	14.5
25	28MM	76.5	76.5	60	18
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		600psi(150℃)	

RS-5116



DN	SIZE	A	B	C	D
15	1/2"	42	77	54	13.5
20	3/4"	44	85	60	17.5
25	1"	50	99.5	70	23.5
32	1 1/4"	57	106	75	30
40	1 1/2"	63	120.5	90	35
50	2"	69	132	100	47
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

STOP VALVE

RS-5117



DN	SIZE	A	B	C	D
15	1/2"	73.5	81	54.5	13
20	3/4"	91.5	100	63	19
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5118



DN	SIZE	A	B	C	D
15	15mm	82.5	81.5	54.5	15
20	20mm	104.5	100	63	22
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5119



DN	SIZE	A	B	C	D
15	1/2"	56	63	50	12
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5120



DN	SIZE	A	B	C	D
15	1/2"	59.5	56.5	54.5	12.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5121



DN	SIZE	A	B	C	D
15	1/2"	47	63	41	9
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5122



DN	SIZE	A	B	C	D
25	1"	73	95.5	63	19
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5123



DN	SIZE	A	B	C	D
15	1/2"	68	104		23
20	3/4"	82	104		30
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5124



DN	SIZE	A	B	C	D
15	1/2"x3/4"		104	50	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to80℃)		5bar(120℃)	

STOP VALVE/PRISECOCK

RS-5125 CONCEALED VALVE



DN	SIZE	A	B	C	D
15	1/2"	55	95		18
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to 110℃)		800psi(150℃)	

RS-5126 CONCEALED VALVE



DN	SIZE	A	B	C	D
15	1/2"	54.5	102		18
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-10℃ to 110℃)		800psi(150℃)	

RS-5127 PRISECOCK/FERRULE



DN	SIZE	A	B	C	D
15	1/2"	79.5	38		15
20	3/4"	92	41.5		19
25	1"	99	47		24
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

RS-5128 PRISECOCK/FERRULE



DN	SIZE	A	B	C	D
15	1/2"	36	82.5		14.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to110℃)		5bar(150℃)	

CHECK VALVE

RS-5129



DN	SIZE	A	B	C	D
15	1/2"	47.5	35.5		14
20	3/4"	56	39		18
25	1"	63	46.5		22
32	1 1/4"	71	51		28
40	1 1/2"	80.5	59.5		33.5
50	2"	93	67		43
65	2 1/2"	105	77		48.5
80	3"	123	81		64
100	4"	162	101		83
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5130



DN	SIZE	A	B	C	D
15	1/2"	56	35		13
20	3/4"	60	38.5		18
25	1"	68	42.5		23.5
32	1 1/4"	76	52		28.5
40	1 1/2"	83	59		33
50	2"	102	64		42
65	2 1/2"	129	81.5		57
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
16		12bar(-10℃ to 80℃)		5bar(110℃)	

RS-5131



DN	SIZE	A	B	C	D
15	1/2"	45.5	36		18
20	3/4"	52	42		23
25	1"	57.5	47		29
32	1 1/4"	62.5	59.5		36
40	1 1/2"	71	66.5		42.5
50	2"	78.5	83		53.5
65	2 1/2"	93	95		66
80	3"	100	110		79
100	4"	112	143		99
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5132



DN	SIZE	A	B	C	D
15	1/2"	58	36		18
20	3/4"	65	42		23
25	1"	74.5	47		29
32	1 1/4"	82	59.5		36
40	1 1/2"	91	66.5		42.5
50	2"	100	83		53.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		400psi(-20℃ to120℃)		800psi(150℃)	

RS-5133



DN	SIZE	A	B	C	D
15	1/2"	51	33		20
20	3/4"	54	38		21
25	1"	62.5	47.5		27.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(110℃)	

RS-5134



DN	SIZE	A	B	C	D
20	3/4"	89.5	42		20
25	1"	100	46.5		25
32	1 1/4"	112	59		32
40	1 1/2"	129	67		40
50	2"	150.5	82		50
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(110℃)	

RS-5135



DN	SIZE	A	B	C	D
15	1/2"	84	33		20
20	3/4"	88	38		21
25	1"	104	47.5		27.5
50	2"	150	82.5		56
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(110℃)	

RS-5136



DN	SIZE	A	B	C	D
15	1/2"	53.5	34		13
20	3/4"	58.5	40		19
25	1"	66.5	52		25
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(110℃)	

FOOT VALVE/Y PATTERN STRAINER

RS-5137 FOOT VALVE



DN	SIZE	A	B	C	D
15	1/2"	77	33		20
20	3/4"	85	38		21
25	2"	97	47.5		27.5

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(110℃)

RS-5138 FOOT VALVE



DN	SIZE	A	B	C	D
25	1"	80.5	51		31
32	1 1/4"	93	60.5		36.5
40	1 1/2"	100	68.5		44
50	2"	117	80		55.5
65	2 1/2"	137.5	100		68
80	3"	174.5	121		81

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(110℃)

RS-5139 Y PATTERN STRAINER



DN	SIZE	A	B	C	D
10	1/4"	54.5	33.5		13
15	1/2"	55.5	33.5		15
20	3/4"	68	39.5		20
25	1"	71.5	44.5		23
32	1 1/4"	96	55		30
40	1 1/2"	105	65.5		34
50	2"	125	73		16

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
32	32bar(-10℃ to110℃)	5bar(150℃)

RS-5140 Y PATTERN STRAINER



DN	SIZE	A	B	C	D
15	1/2"	78	43.5		16
20	3/4"	89	46		18
25	1"	103	60		27
32	1 1/4"	136	77		32
40	1 1/2"	151.5	82		37
50	2"	184	112		54
65	2 1/2"	218	132		61.5

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
32	32bar(-10℃ to110℃)	5bar(150℃)

FLOAT VALVE

RS-5141



DN	SIZE	A	B	C	D
15	1/2"	52.5			8.5

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(120℃)

Male thread according ISO 228/1

RS-5142



DN	SIZE	A	B	C	D
15	1/2"	65.5			7
20	3/4"	65.5			7

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(120℃)

Male thread according ISO 228/1

RS-5143



DN	SIZE	A	B	C	D
15	1/2"	74		265	4
20	3/4"	81		322	6.5
25	1"	92		356	9.5
32	1 1/4"	104.5		392	12
40	1 1/2"	111		415	17
50	2"	123		445	20

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(120℃)

Male thread according ISO 228/1

RS-5144

RS-5145



DN	SIZE	A	B	C	D
15	1/2"	93		238.5	4.5
20	3/4"	93		238.5	4.5

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(120℃)

Male thread according ISO 228/1

RS-5146



DN	SIZE	A	B	C	D
15	1/2"	74		265	4
20	3/4"	81		322	6.5

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(120℃)

Male thread according ISO 228/1

RS-5147



DN	SIZE	A	B	C	D
15	1/2"	67.5		240	8
20	3/4"	70.5		308.5	8
25	1"	83		314.5	12.5

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
12	12bar(-10℃ to 80℃)	5bar(120℃)

Male thread according ISO 228/1

RS-5148



DN	SIZE	A	B	C	D
15	1/2"	75		238	6
20	3/4"	75		285	6
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(120℃)	

Male thread according ISO 228/1



DN	SIZE	A	B	C	D
15	1/2"	64.5		204	8.5
20	3/4"	67		216.5	10
25	1"	81		289.5	12.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(120℃)	

Male thread according ISO 228/1

ISO9001 TUV SGS CE ACS WRAS

RS-5149



SIZE	A	B	C	D
1"x2	110	50	1"	1/2"
1"x3	160	50	1"	1/2"
1"x4	210	50	1"	1/2"
1"x5	260	50	1"	1/2"
Pressure and temperature limitations for PN rated valve				
PN	Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa	-20℃ to 100℃		120℃	

RS-5150



SIZE	A	B	C	D
3/4"x2	74	28.5	34.5	20.5
3/4"x3	125	28.5	35	18
3/4"x4	168.5	28.5	35	19
3/4"x5	196	28.5	35	19
Pressure and temperature limitations for PN rated valve				
PN	Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa	-20℃ to 100℃		120℃	

MANIFOLD

RS-5151



SIZE	A	B	C	D
3/4"x2	87	37	35	20.5
3/4"x3	121	37	35	20.5
3/4"x4	157	37	35	20.5
Pressure and temperature limitations for PN rated valve				
PN	Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa	-20℃ to 100℃		120℃	

RS-5152



SIZE	A	B	C	D
3/4"x2	86	59.5	36	20
3/4"x3	125	59.5	36	20
3/4"x4	158	59.5	36	20
1"x3	94	61.5	36	28
1"x4	127	61.5	36	28
1"x5	162	61.5	36	28
Pressure and temperature limitations for PN rated valve				
PN	Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa	-20℃ to 100℃		120℃	

RS-5153



SIZE	A	B	C	D	E
1"x2	107	59	36	16	46
1"x3	154	59	36	16	46
1"x4	200	59	36	16	46
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		-20℃ to 100℃		120℃	

MANIFOLD

RS-5154



SIZE	A	B	C	D	E
1"x2	107	59	36	16	46
1"x3	154	59	36	16	46
1"x4	200	59	36	16	46
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
≤ 1.6Mpa		-20℃ to 100℃		120℃	

ISO9001 TUV SGS CE ACS WRAS

RS-5155





SIZE	A	B	C	D
1 1/4"x1525				
1 1/4"x2520				
1 1/4"x3520	136.5	115	86	49

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	-20℃ to 100℃	120℃

RS-5156





	B	C	D	E
5	36.5	46	17	10.2

and temperature limitations for PN rated valve

	Pressure and temperature range	Pressure and Max temperature
	-20℃ to 100℃	120℃

ANGLE VALVE

RS-5157





DN	SIZE	A	B	C	D
15	3/8"x1/2"	28	77	29	9
15	1/2"x1/2"	29	77	29	9
15	1/2"x3/4"	30	80	30.5	9

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5158





DN	SIZE	A	B	C	D
15	3/8"x1/2"	29	82	33	9
15	1/2"x1/2"	31	82	33	9
15	1/2"x3/4"	34	85	37	11

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5159





DN	SIZE	A	B	C	D
15	1/2"x1/2"	151.5	64	43.5	44

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5160





DN	SIZE	A	B	C	D
15	3/8"x1/2"	27	76	35	7
15	1/2"x1/2"	27	76	35	7
15	1/2"x3/4"	30	81	40	9

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5161





DN	SIZE	A	B	C	D
15	1/2"	50.5	45.5		16

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	400psi(-10℃ to 110℃)	800psi(150℃)

RS-5162





DN	SIZE	A	B	C	D
15	3/8"x1/2"	43	60	26	10
15	1/2"x1/2"	45	60	26	10
15	1/2"x3/4"	45	68	30.5	10

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5163





DN	SIZE	A	B	C	D
15	1/2"x1/2"	43	62	38	16
15	1/2"x3/4"	43	62	38	16

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5164





DN	SIZE	A	B	C	D
15	1/2"x1/2"	106	50	69	33

Pressure and temperature limitations for PN rated valve

PN	Pressure and temperature range	Pressure and Max temperature
≤ 1.6Mpa	16bar(-10℃ to 80℃)	5bar(150℃)

RS-5165





DN	SIZE	A	B	C	D
15	3/8"x1/2"	33.5	71	31.5	9
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		16bar(-10℃ to 90℃)		5bar(150℃)	

RS-5166





DN	SIZE	A	B	C	D
15	1/2"x3/8"	32	90	38.5	10
15	1/2"x1/2"	36	117	61	11.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		16bar(-10℃ to 80℃)		5bar(150℃)	

RS-5167





DN	SIZE	A	B	C	D
15	3/8"x1/2"	26.5	65	28.5	6
15	1/2"x1/2"	26.5	65	28.5	6
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		16bar(-10℃ to 80℃)		5bar(150℃)	

RS-5168





DN	SIZE	A	B	C	D
15	3/8"x1/2"	48	60	23	8.5
15	1/2"x1/2"	48	60	23	8.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		16bar(-10℃ to 80℃)		5bar(150℃)	

RS-5169





DN	SIZE	A	B	C	D
15	1/2"x1/2"	67	66	45	17
20	3/4"x3/4"	78	70.5	45	21
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
10		10bar(0℃ to 90℃)		10bar(90℃)	

RS-5170





DN	SIZE	A	B	C	D
15	1/2"x1/2"	84	52	45	14
20	3/4"x3/4"	92	58	45	14
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
10		10bar(0℃ to 90℃)		10bar(90℃)	

RS-5171





DN	SIZE	A	B	C	D
15	1/2"	80	62	39.5	10
20	3/4"	85	67	39.5	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
10		10bar(0℃ to 90℃)		10bar(90℃)	

RADIATOR/THERMOSTATIC VALVE

RS-5173





DN	SIZE	A	B	C	D
15	1/2"x1/2"	75.5	115	80	16
20	3/4"x3/4"	80	118	85	19
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
10		10bar(0℃ to 90℃)		10bar(90℃)	

RS-5174





DN	SIZE	A	B	C	D
15	1/2"	50.5	132	50	11
20	3/4"	55	135	50	15
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
10		10bar(0℃ to 90℃)		10bar(90℃)	

RS-5175





DN	SIZE	A	B	C	D
15	1/2"	48	47		11
20	3/4"	56	52		16
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to 110℃)		5bar(150℃)	

RS-5172



DN	SIZE	A	B	C	D
15	1/2"	87	115	50	15
20	3/4"	91.5	118	50	20
25	1"	106.5	123	50	25
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
10		10bar(0℃ to 90℃)		10bar(90℃)	

RS-5176



DN	SIZE	A	B	C	D
15	1/2"	67	29.5		11
20	3/4"	77	37.5		16
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to 110℃)		5bar(150℃)	

PRESSURE REDUCING VALVE

RS-5177



DN	SIZE	A	B	C	D
15	1/2"	39.5	43	26.5	9.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to 110℃)		5bar(150℃)	

RS-5178



DN	SIZE	A	B	C	D
15	1/2"	42	35.5	26.5	11.5
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to 110℃)		5bar(150℃)	

RS-5179



DN	SIZE	A	B	C	D
15	1/2"	45	68		
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(150℃)	

RS-5180



DN	SIZE	A	B	C	D
15	1/2"	45	68		
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(150℃)	

RS-5181



DN	SIZE	A			
20	3/4"	37			
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5182



DN	SIZE	A	B	C	D
20	3/4"	158	149		
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
12		12bar(-10℃ to 80℃)		5bar(120℃)	

RS-5183



DN	SIZE	A	B	C	D
10	7/16"	121	7/16"	7/16"	6
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to 110℃)		5bar(150℃)	

RS-5184



DN	SIZE	A	B	C	D
25	1"	155	44.5		
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
32		32bar(-10℃ to 110℃)		5bar(150℃)	

RS-5185



DN	SIZE	A	B	C	D
15	1/2"	90	68.2	31	
Pressure and temperature limitations for PN rated valve					
PN		Pressure and temperature range		Pressure and Max temperature	
< 1.6Mpa		400psi(-10℃ to 110℃)		800psi(150℃)	

Pipe Fitting

RS-5186





1/2"

DN	SIZE	A	B	C	D
15	1/2"	62.5	73.5		
Pressure and temperature limitations for PN rated valve					
PN	Pressure and temperature range		Pressure and Max temperature		
< 1.6Mpa	400psi(-10℃ to 110℃)		800psi(150℃)		

RS-5187





DN	SIZE	A	B	C	D
15	1/2"	51	85	G1/2	
20	3/4"				
Pressure and temperature limitations for PN rated valve					
PN	Pressure and temperature range		Pressure and Max temperature		
< 1.6Mpa	400psi(-10℃ to 110℃)		800psi(150℃)		

RS-5188





DN	SIZE	A	B	C	D
15	1/2"	70	72		
Pressure and temperature limitations for PN rated valve					
PN	Pressure and temperature range		Pressure and Max temperature		
32	32bar(-10℃ to 110℃)		5bar(150℃)		

P/N	DN
STRAIGHT	16X1/2F 22X3/4F 28X1F

P/N	DN
STRAIGHT	16X16 20X20

P/N	DN
ELBOW	16X1/2 18X1/2

P/N	DN
ELBOW	16X16 20X20

P/N	DN
TEE	18X18X1/2F 22X22X3/4F

P/N	DN
TEE	16X16X16 20X20X20

P/N	DN
STRAIGHT	15X1/2F 22X3/4F 28X1F

P/N	DN
STRAIGHT	20X1/2M 25X1M 32X1M

P/N	DN
ELBOW	15X1/2F 22X3/4F 28X1F

P/N	DN
ELBOW	20X20 25X25 32X32

P/N	DN
TEE	15X15X15 22X22X22 28X28X28

P/N	DN
TEE	20X20X1/2M 25X25X3/4M 32X32X1M

Pipe Fitting

P/N	DN
STRAIGHT	15X22 22X35

P/N	DN
STRAIGHT	1/2X1/2 3/4X3/4 1X1

P/N	DN
ELBOW	15X15 22X22 35X35

P/N	DN
ELBOW	1/2X1/2 3/4X3/4 1X1

P/N	DN
TEE	15X15X15 22X22X22 35X35X35

P/N	DN
TEE	1/2X1/2X1/2 3/4X3/4X3/4 1X1X1

P/N	DN
STRAIGHT	16X1/2M
	20X3/4M
	26X3/4M

P/N	DN
STRAIGHT	1/2X10mm
	1/2X20mm
	1/2X30mm

P/N	DN
ELBOW	16X1/2M
	20X3/4M
	26X3/4M

P/N	DN
INSERTS	1/2F
	3/4F
	1F

P/N	DN
TEE	16X16X1/2M
	20X20X3/4M
	26X26X3/4M

P/N	DN
ELBOW	15X1/2F
	22X3/4F
	28X1F

NOTE

江山市瑞申机械有限公司

JIANGSHAN RISEN MACHINE CO.,LTD

地址：江山市经济开发区江东区兴工北路30号
Add: NO.30 Xinggongbei Rd. Jiangshan, Zhejiang,
PRC P.C.:324000
Tel 电话: +86-570-3046655 +86-570-4982666
+86-13757002268 +86-13867008826
Fax传真：+86-570-3046633
E-mail : risen@risenmachine.com
Website：http://www.risenmachine.com